

SURFACE COATING SEALER

FOR INTERIOR / EXTERIOR APPLICATION

The surface coating sealer is highly diffusive preservative. It significantly reduces the suction capacity of the material, strengthens loose surface and prevents salt efflorescence (layering salt). It is intended for use both indoors and outdoors. It functions in depth and after drying is transparent. The material is still breathable after application. The surface coating sealer is needed to restore in the exterior of every 8 - 10 years. The interior repainting is not required.

GUIDELINES FOR PROCESSING:

Sealer in the bottle is needed to be thoroughly mixed before use. Pour out about half the contents of the bottle into prepared container. Then close the bottle and shake well. Empty out the entire contents of the bottle into prepared container. Apply sealer by paint roller after drying the adhesive substance/glue. Adhesive substance/glue dries at least 24 hours. Do not apply sealer at temperatures below + 10°C.

TEMPERATURE PROCESSING:

Minimum recommended temperature is + 10°C for air and base for the application of X-STONE® tiles. When used in the exterior and using adhesives for exterior mind and take care of the values specified by the manufacturer of adhesives.

STORAGE AND EXPIRATION:

Store in a cool, dry place, but not at temperatures below + 5°C. Expiration is at optimal storage at least 12 months.

Keep out of reach of children !

DRYING:

At temperature + 20°C, and assuming 65% relative humidity around 10 - 15 hours.

CONSUMPTION:

Cca 300 ml/m²

PACKING:

1 liter - surface coating sealer interior / exterior

500 ml - waterproof surface coating sealer

CONTENTS:

acrylic sealant, water, admixtures, preservative

Made in Germany.